4" SILVER LINE SERIES

Performance Table

C.R.I. PUMPS
Pumping trust. Worldwide.

Pump model	Motor kW	lps / m³/h	0 / 0	0.20 / 0.75	0.27 / 1	0.34 / 1.25	0.41 / 1.5	0.48 / 1.75	0.55 / 2	0.69 / 2.5	0.83 / 3	0.97 / 3.5	1.1 / 4	1.25 / 5	1.66 / 6	1.94 / 7	2.22 / 8	2.78 / 10	3.33 / 12	3.89 / 14	4.44 / 16	5 / 18	5.56 / 20	6.11 / 22	OUTLET SIZE IN INCHES	NET WEIGHT in kg
S4P-1E/08	0.37	Head in meters	54	46	42	38	32	24	15																1¼	3.3
S4P-1E/13	0.55		89	78	75	70	61	50	38																1¼	4.2
S4P-1E/17	0.75		116	101	94	84	73	59	43																1¼	5
S4P-1E/18	0.75		122	111	102	93	81	67	49																1¼	5.3
S4P-1E/25	1.1		166	148	135	118	101	81	59																1¼	8.8
S4P-1E/26	1.1		177	156	143	127	109	89	68																1¼	9
S4P-1E/33	1.5		220	199	179	160	136	112	88																1¼	11.6
S4P-1E/34	1.5		226	202	188	172	149	124	98																1¼	12
S4P-2/05	0.37	Head in meters	44		40	39	38	35	31	25	13														1¼	2.8
S4P-2/07	0.55		62		59	56	52	49	45	34	22														1¼	3.1
S4P-2/11	0.75		98		90	87	82	77	70	53	35														1¼	3.8
S4P-2/16	1.1		143		131	127	119	112	100	78	48														1¼	6.5
S4P-2/22	1.5		194		172	165	153	142	129	100	65														1¼	7.7
S4P-2/30	2.2		260		232	223	209	192	172	135	92														1¼	10.5
S4P-3/07	0.55	Head in meters	52						42	38	33	26	18	2											1¼	2.8
S4P-3/08	0.55		59						52	45	39	31	22	4											1¼	3.4
S4P-3/11	0.75		80						70	62	54	45	34	8											1¼	3.9
S4P-3/15	1.1		111						98	88	77	63	48	12											1¼	4.9
S4P-3/20	1.5		150						128	116	101	82	61	13											1¼	7.9
S4P-3/21	1.5		157						133	121	107	86	63	15											1¼	8.2
S4P-3/28	2.2		208						177	161	141	115	88	22											1¼	10.9
S4P-3/30	2.2		221						190	172	151	125	96	26											1¼	11.7
S4P-4/05	0.55	Head in meters	38						32	31	28	26	22	15	8										1¼	1.9
S4P-4/06	0.55		46						40	38	37	34	31	21	12										1¼	2.4
S4P-4/07	0.75		54						49	47	44	41	37	25	14										1¼	3.3
S4P-4/10	1.1		79						69	66	62	57	51	39	22										1¼	4
S4P-4/11	1.1		86						77	77	72	67	61	47	29										1¼	4.4
S4P-4/14	1.5		110						99	85	89	82	73	55	35										1¼	5.6
S4P-4/15	1.5		118						108	102	96	88	79	60	38										1¼	6
S4P-4/20	2.2		158						141	135	128	119	110	82	49										1¼	8
S4P-4/22	2.2		185						165	156	148	138	128	98	58										1¼	8.8
S4P-4/27	3		210						198	182	183	172	159	120	71										1¼	10.8
S4P-4/35	3.7		270						248	237	228	210	192	140	81										1¼	14
S4P-5/06	0.75	Head in meters	42								39	37	37	32	27	18	9								1¼	3.4
S4P-5/08	1.1		58								53	52	49	42	34	25	15								1¼	2.3
S4P-5/09	1.1		65								59	57	55	50	41	31	17								1¼	3
S4P-5/11	1.5		79								72	69	67	58	48	35	20								1¼	3.5
S4P-5/12	1.5		86								78	76	73	65	55	42	25								1¼	4.3
S4P-5/17	2.2		123								115	110	105	91	76	57	31								1¼	4.8
S4P-5/21	3		145								135	121	126	111	92	70	39								1¼	6.6
S4P-5/27	3.7		184								163	157	158	138	116	80	42								1¼	8.2
S4P-8/04	0.75	Head in meters	25										21	22	20	20	19	14	8						2	3.8
S4P-8/06	1.1		38										35	34	32	31	28	22	13						2	4.4
S4P-8/08	1.5		51										48	47	45	43	40	31	20						2	3.2
S4P-8/13	2.2		82										72	71	69	65	61	48	29						2	6.5
S4P-8/17	3		108										101	99	96	91	85	69	43						2	7.9
S4P-8/23	4		143										132	128	122	116	109	88	52						2	10
S4P-8/32	5.5		200										182	175	168	159	148	116	68						2	13
S4P-8/43	7.5		270										242	233	221	210	193	149	88						2	17.5
S4P-10/03	0.75	Head in meters	17										16	16	15	14	14	12	9	5					2	2.72
S4P-10/04	0.75		22										21	21	20	19	18	16	13	7					2	3
S4P-10/05	1.1		27										26	26	25	24	23	20	16	9					2	4.3
S4P-10/06	1.1		34										33	32	31	30	28	24	19	12					2	5.1
S4P-10/07	1.5		39										37	37	35	34	33	28	22	14					2	5.5
S4P-10/08	1.5		46										43	43	42	40	38	33	27	12					2	6
S4P-10/10	2.2		57										54	53	52.5	50	48	42	33	22					2	7.6
S4P-10/12	2.2		66										64	64	62.5	60	57	50	39	25					2	9.1
S4P-10/15	3		83										78	77	75	73	69	61	48	33					2	11.3
S4P-10/17	3		94										88	87	84	82	78	69	55	39					2	11.8
S4P-10/20	4		107										102	101	98	96	92.5	82	65	45					2	12.8
S4P-10/22	4		122										116	113	111	109	102.5	90	72	50					2	16.6
S4P-10/26	5.5		140										136	133	130	126	122	107	85	59					2	19.6
S4P-10/28	5.5		153										144	142	137	133	127	112	91	65					2	21.1
S4P-14/03	0.75	Head in meters	17														14	13	12	9	7				2	2.6
S4P-14/05	1.1		28														24	22	19	16	14	9	6		2	4.3
S4P-14/07	1.5		38														33	30	26	22	18	14	9		2	6
S4P-14/10	2.2		59														49	45	40	34	29	22	15		2	8.5
S4P-14/11	2.2		64														59	50	45	39	33	25	17		2	9.7
S4P-14/12	3		69														59	55	48	43	34	27	18		2	10.2
S4P-14/13	3		74														65	58	52	44	36	29	20		2	11
S4P-14/16	3.7		89														77	69	62	53	44	34	24		2	13.6
S4P-14/17	3.7		98														85	77	68	59	49	38	27		2	14.4
S4P-14/22	5.5		123														104	93	82	70	57	43	29		2	29
S4P-14/24	5.5		134														114	104	92	78	64	49	33		2	33
S4P-18/04	1.1	Head in meters	17															14	13	11	10	9	8	6	2	3.8
S4P-18/06	1.5		26															19	18	17	16	14	11	9	2	5
S4P-18/09	2.2		38															31	29	27	24	21	17	14	2	6.5
S4P-18/13	3.7		54															45	42	38	34	28	24	20	2	9.8
S4P-18/14	4		58															48	44	41	37	33	27	23	2	10.5
S4P-18/20	5.5		81															68	63	57	52	46	38	30	2	15.5
S4P-18/22	5.5		89															74	71	61	55	48	41	32	2	18
S4P-18/26	7.5		106															90	84	76	67	57	47	38	2	19.1
S4P-18/28	7.5		116															97	89	82	73	64	54	43	2	22

Shuft off head | Maximum & Minimum operating limits | Recommended working head | Best Efficiency at duty point

In view of continuous developments, the information / descriptions / specifications / illustrations are subject to change without notice.

C.R.I. PUMPS S.A. (PTY) LIMITED
P.O. Box 6292, Halfway House, Midrand - 1685, Johannesburg, South Africa. Tel : +27-11-8058631 / 32 , Fax : +27-11-8058630, e-mail : cri@cripumps.co.za website : www.cripumps.com
Branches : Pietermaritzburg, Tel : +27-33-3453944 | Capetown, Tel : +27-21-9312516