



C.R.I. PUMPS
Pumping trust. Worldwide.

Technical Data

Pump Model
MVS-66/07T

Project Name : Untitled project 2025-03-18 12:28:21.412	Project ID :
Company Name : Department : Phone number : e-mail address :	

Requested Data

Flow : 65.69 m ³ /h Head : 166.4 m	Fluid : Water Density : 0.9983 kg/dm ³ Viscosity : 1.005 mm ² /s Temperature : 20 °C Vapour pressure at t A : 0.0234 bar
--	---

Pump

Operating Data

Pump Model : MVS-66/07T No. of Stages : 7 Inlet / Outlet size : 100 Speed : 2900 1/min Direction of Rotation : Counter clockwise Impeller type : Radial impeller Impeller Design : Closed Pump Weight (Approx) : 121.5 kg Pump Standard : CRI Standard	Flow : 65.61 m ³ /h Head : 166 m Shutoff Head : 208.3 m Efficiency : 79.26 %
---	--

Motor

Motor Model : MV 3P 60.0HP (IE2) Frequency/Efficiency class : 50 Hz IE2 = High Efficiency Rated Voltage : 380V-415V Δ / 660V-720V λ Rated current : 80.0A / 46.2A Phase / Rated Power P2 : 3~ 45 kW Speed : 2955 1/min Efficiency : 92.9 % Motor Weight (Approx) : 331 kg Motor Standard : IEC-60034-30 / IS-12615	Insulation Class : F Frame size : 225M Degree of Protection : IP 55 Method of Starting : Star-delta Service factor : 1 Power factor : 0.88
---	---

Material of Construction

Flange Connections

Pump Outer Shell : AISI 304 Pump Head : AISI 304/CF8 Pump Head Stool : C.I Pump Base : AISI 304/CF8 Base Plate : C.I Impeller : AISI 304 MECHANICAL SEAL : SiC/SiC/FKM Bush : SiC / SiC Diffuser (Chamber) : AISI 304 Pump Shaft : AISI 431 Wearing Ring : Teflon FLANGE : C.I Neck Ring : AISI 304 O Ring : EPDM Coupling : C.I Split Cone : AISI 304	Suction Flange Pressure rating : PN 40 Nominal pipe size : DN 100 Standard : DIN EN 1092-1:2008-09 Discharge Flange Pressure rating : PN 40 Nominal pipe size : DN 100 Standard : DIN EN 1092-1:2008-09
---	--



C.R.I. PUMPS
Pumping trust. Worldwide.

Performance Curve

Pump Model
MVS-66/07T

Project Name : Untitled project 2025-03-18 12:28:21.412

Project ID :

Company Name :


Department :

Phone number :

e-mail address :

Curve Tolerance ISO : 9906, Grade-3B

Speed 2900 rpm






Project Name : Untitled project 2025-03-18 12:28:21.412

Project ID :

Company Name :
Department :
Phone number :
e-mail address :



In View of continuous developments, The information/specifications/Description/ Illustrations are subject to change without notice.

Dimensions inmm

L1	1148		
L2	656		
OD	400		
X	326		
Y	402		
Z	305		