



Technical Data

Project Name : Untitled project 2025-03-22 10:19:23.013	Project ID :
Company Name : Department : Phone number : e-mail address :	

Requested Data

Flow : 209.1 m ³ /h	Fluid : Water
Head : 33.05 m	Density : 0.9983 kg/dm ³
	Viscosity : 1.005 mm ² /s
	Temperature : 20 °C

Pump

Operating Data

Pump Model : ECW 100/315	Flow : 209.1 m ³ /h
Inlet / Outlet size : 125x100	Head : 33.05 m
Speed : 1450 1/min	Shutoff Head : 39 m
Direction of Rotation : Clockwise from the drive end	Shaft Power (BkW) : 23.07 kW
Impeller type : Radial impeller	End of Power curve : 30.2 kW
Impeller Diameter : 338 mm	Efficiency : 81.5 %
Min.Impeller Diameter : 270 mm	NPSHr Value : 2.511 m
Max.Impeller Diameter : 338 mm	Moment of Inertia : 1.298 kg m ²
Maximum Solid Size : 56 mm	Operating Pressure : 3.237 bar
Pump Weight (Approx) : 115 kg	Maximum Allowable Pressure : 3.819 bar
Pump Standard : EN 733	Minimum Continuous Flow : 62.4 m ³ /h

Motor

Frequency : 50 Hz	Speed : 1465 1/min
Phase : 3~	Degree of Protection : IP 55
Rated Voltage : 415 V	Insulation Class : F
Rated current : 54 A	Frame size : 200 L
Rated Power P2 : 30 kW	

Material of Construction

Flange Connections

Casing : ASTM A743 / A351 CF8	Suction Flange
Impeller : ASTM A743 / A351 CF8	Pressure rating : 16 bar
Stuffing Box : ASTM A743 / A351 CF8	Nominal pipe size : 125
Wear Ring : ASTM A743 / A351 CF8	Standard : PN 16
Bearing Frame : ASTM A48 class 30B	
Shaft : ASTM A276 AISI 304	Discharge Flange
Shaft Sleeve : ASTM A276 AISI 304	Pressure rating : 16 bar
Shaft seal : GLAND PACKING	Nominal pipe size : 100
	Standard : PN 16



C.R.I. PUMPS
Pumping trust. Worldwide.

Performance Curve

Pump Model
ECW 100/315

Project Name : Untitled project 2025-03-22 10:19:23.013

Project ID :


Company Name :

Department :

Phone number :

e-mail address :

Curve Tolerance ISO 9906 Grade 2B



Note:

- Performance is not guaranteed except for the rated point.
 - Curves specified are as per Specific gravity and viscosity of water 1.0,
 - Consider NPSH safety margin minimum of 0.5m .
- To select the motor size, read the value of the Power curve at the duty point



C.R.I. PUMPS
Pumping trust. Worldwide.


Dimensional Drawing

Pump Model
ECW 100/315

Project Name : Untitled project 2025-03-22 10:19:23.013

Project ID :

Company Name :
Department :
Phone number :
e-mail address :



In View of continuous developments, The information/specifications/Description/ Illustrations are subject to change without notice.

Dimensions in mm

a	140			H.D-Discharge	19
b1	450			H.D-Suction	19
b2	420			No.of Holes-Discharge	8
f	470			No.of Holes-Suction	8
H	345			Nominal Size (ØA)	125
h2	315			Nominal Size (ØB)	100
hA	270			P.C.D-Discharge	180
L1	1285			P.C.D-Suction	210
L2	1085				
L3	542.5				
Ø A	125				
Ø B	100				
S	14				
X	140				
Z	6				