



Technical Data

Project Name : Untitled project 2025-03-22 10:19:23.013	Project ID :
Company Name : Department : Phone number : e-mail address :	

Requested Data

Flow : 321.1 m ³ /h	Fluid : Water
Head : 54.02 m	Density : 0.9983 kg/dm ³
	Viscosity : 1.005 mm ² /s
	Temperature : 20 °C

Pump

Operating Data

Pump Model : ECW 125/400	Flow : 321.1 m ³ /h
Inlet / Outlet size : 150x125	Head : 54.02 m
Speed : 1450 1/min	Shutoff Head : 62 m
Direction of Rotation : Clockwise from the drive end	Shaft Power (BkW) : 57.13 kW
Impeller type : Radial impeller	End of Power curve : 71 kW
Impeller Diameter : 420 mm	Efficiency : 82.56 %
Min.Impeller Diameter : 336 mm	NPSHr Value : 4.941 m
Max.Impeller Diameter : 420 mm	Moment of Inertia : 3.461 kg m ²
Maximum Solid Size : 33 mm	Operating Pressure : 5.29 bar
Pump Weight (Approx) : 183 kg	Maximum Allowable Pressure : 6.072 bar
Pump Standard : EN 733	Minimum Continuous Flow : 95.4 m ³ /h

Motor

Frequency : 50 Hz	Speed : 1450 1/min
Phase : 3~	Degree of Protection : IP 55
Rated Voltage : 415 V	Insulation Class : F
Rated current : 130 A	Frame size : 280SX
Rated Power P2 : 75 kW	

Material of Construction

Flange Connections

Casing : ASTM A743 / A351 CF8	Suction Flange
Impeller : ASTM A743 / A351 CF8	Pressure rating : 16 bar
Stuffing Box : ASTM A743 / A351 CF8	Nominal pipe size : 150
Wear Ring : ASTM A743 / A351 CF8	Standard : PN 16
Bearing Frame : ASTM A48 class 30B	
Shaft : ASTM A276 AISI 304	Discharge Flange
Shaft Sleeve : ASTM A276 AISI 304	Pressure rating : 16 bar
Shaft seal : GLAND PACKING	Nominal pipe size : 125
	Standard : PN 16



C.R.I. PUMPS
Pumping trust. Worldwide.

Performance Curve


Pump Model
ECW 125/400

Project Name : Untitled project 2025-03-22 10:19:23.013

Project ID :

Company Name :
Department :
Phone number :
e-mail address :

Curve Tolerance ISO 9906 Grade 2B



Note:

- Performance is not guaranteed except for the rated point.
 - Curves specified are as per Specific gravity and viscosity of water 1.0,
 - Consider NPSH safety margin minimum of 0.5m .
- To select the motor size, read the value of the Power curve at the duty point



C.R.I. PUMPS
Pumping trust. Worldwide.


Dimensional Drawing

Pump Model
ECW 125/400

Project Name : Untitled project 2025-03-22 10:19:23.013

Project ID :

Company Name :
Department :
Phone number :
e-mail address :



In View of continuous developments, The information/specifications/Description/ Illustrations are subject to change without notice.

Dimensions in mm

a	140			H.D-Discharge	19
b1	620			H.D-Suction	23
b2	590			No.of Holes-Discharge	8
f	530			No.of Holes-Suction	8
H	435			Nominal Size (ØA)	150
h2	400			Nominal Size (ØB)	125
hA	335			P.C.D-Discharge	210
L1	1700			P.C.D-Suction	240
L2	1500				
L3	750				
Ø A	150				
Ø B	125				
S	18				
X	140				
Z	6				